

DL208T

Two-way loudspeaker system

The DL208T is a compact, 8" coaxial driver, 2-way, highly weather-resistant, full range loudspeaker with high SPL, the body is made of engineering plastic injection molding. The system conforms to IP56 international standard. DL208T is equipped with multi-tap transformer based on DL208T.



FEATURES

- Highly weather-resistant IP56 rating
- Engineering plastic injection molding
- High SPL
- Coaxial components design
- Good used for sports facilities, stadiums, water parks, outdoor background music, swimming pools and a wide variety of other outdoor and indoor venue types.

Technical specifications

FREQUENCY RESPONSE (-10dB)	80Hz-18kHz
DRIVERS	1×8" (200mm)/2" voice coil LF 1×1" (25mm) /1.4" voice coil HF
INPUT VOLTAGE	100V
POWER	37.5W/75W/150W/OFF/8Ω
SENSITIVITY	96 dB 1 watt/1 metre
MAXIMUM SPL	118 dB continuous, 124dB peak
IMPEDANCE	8 ohms nominal
DISPERSION(-6 dB)	90°×90°
CROSSOVER	2.3 kHz passive
INPUT CONNECTORS	Covered barrier strip terminals
DIMENSIONS	(W)300mm×(H)302mm×(D)345mm
WEIGHT	11 kg

Overall Dimensions

