

VERTEX[®]

Digital Sound System



Touch Up Your Sound System
and Dream To It.

Mixing Amplifier



Model : MA-2300

Feature

- Five Microphone input, two auxiliary and one Lineout for recorder.
- Treble and Bass Volume Control.
- Build in Speaker Protection Circuit and output short circuit.
- Build in FM radio and MP3 player.
- Mic. Control can adjust Treble, Bass and Echo tone



Model : V1

Specifications

Model	MA-2300
Power Output	80 watts (40 watts + 40 Watts)
Input	5 x Microphone 2 x AUX 1 x USB (MP3) 1 x SD/MMC Slot 1 x FM radio 1 x Line out
Output	Echo. / Treble / Bass / Mic.Vol
Mic.Volume	Treble / Bass / Balance
Volume Adjustable	50 Hz - 20 kHz
Frequency Response	Less than 0.5% (@1kHz, 1/3 power output)
Distortion	LED
Power Indicator	Yes
Speaker Protection	AC fuse and Output shot-circuit
Protection	AC 200 - 240 V 50/60Hz
Power Supply	483 x 230 x 88 mm.
Dimension	2U size
Installation	

Specifications

Model	V1
Mic Capsule	Dynamic
Polar Pattern	Cardioid
Frequency Response	70 Hz - 16 kHz
Sensitivity	- 52 dB
Output Impedance	500 Ohm
Weight	334 g.
Dimension	51.5 x 183 mm.
Output connector	Three-pin professional audio (XLR), male

Conference System



Model : CS-A6300K

Feature

- Telephone port is ready for plug in and use for conference.
- Two remote conference system be able to join via land line.
- Number of simultaneously usable delegate units can be set to 3 or 6 units.
- Easy plug-and-play installation: one-cable, daisy-chain connectivity.
- Two conference group and each group connect upto 30 conference units.
- Voice tone and level are able to adjust as need.
- Be able to connect to other voice recorder.

Specifications

Model	CS-A6300K
Max current consumption	450 mA
Mic. input	Round DIN-8P (x2)
Audio out	Balance port x 1 (XLR) No Balance port x 1 (Phone jack) Rec. output port x 1 (RCA) Line output port x 1 (RCA) RJ 11 (Ready to use)
Telephone port	On-Off volume with voice level control.
Telephone control	Treble, Bass and Sound level
Volume Adjustable	3 or 6
Delegate Limit Control	50 Hz - 20 KHz
Frequency Response	70 dB
S/N ratio	483 x 218 x 45 mm.
Dimension	1U size
Installation	

Specifications

Model	BH-A5010	BH-A5020
Type	Chairman Unit	Delegate Unit
Priority Control	Yes	No
Connector	Round DIN-8P	Round DIN-8P
Power Supply	DC 18 V (by controller unit.)	DC 18 V (by controller unit.)
Current Consumption	40 mA	40 mA
Sensitivity	-47 dB/Pa	-47 dB/Pa
Frequency Response	70 Hz - 15 kHz	70 Hz - 15 kHz
Polar Pattern	Unidirectional (Super-cardioid)	Unidirectional (Super-cardioid)



Model : BH-A5020

Model : BH-A5010



Tel : 0-2938-1424

*** All product specifications are subject to change without prior notice.

VERTEX is a trademark of Vertex Supply Co.,Ltd. Thailand, who has received ISO9001 certified under the global standard for quality management.