

The P-2240 is power amplifier featuring high cost performance suit for paging applications in schools, churches, offices and retail stores.



Order no: P-2240 H
Alternative products: A-2030, A-2060, A-2120, A-2240

Specifications

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power source | 220 - 240 V AC, 50 / 60 Hz |
| Rated output | 240 W |
| Frequency response | 50 Hz - 20 kHz |
| Distortion | < 1 % (at 1 kHz, 1/3 rated output power) |
| Power consumption | 520 W (AC) |
| S/N ratio | 60 dB |
| Inputs | Line-in 0 dBV, 10 k Ω , balanced, screw terminal 100 V line in: 40 dBV, 330 k Ω , unbalanced, screw terminal Power remote control: Make contact |
| Outputs | Loop out: 0 dBV, 10 k Ω , balanced, screw terminal Speaker out: Balanced (floating) High impedance: 42 Ω (100 V), 21 Ω (70 V) Low impedance: 4 Ω (31 V) |
| Number of channels | 1 |
| Indicator | Power, signal, peak |
| Weight | 13,2 kg |
| Dimensions (W x H x D) | 420 x 100,9 x 351,3 mm |
| Dimensions (ϕ x D) | x 351,3 mm |
| Gross weight | 14,5 kg |
| Finish | ABS resin, Steel plate, black |

Appearance

