

PC-1860EN

The ceiling speakers of the PC-series are suitable for announcements and BGM system use in high quality. The speaker's design harmonizes with modern architecture and decor. The PC-1860EN is designed according to EN54-24.



Order no: PC-1860EN
 Alternative products: VM-3360VA,
 VM-3240VA, VP-2421, VP-2421incl, VP-2241,
 VP-2241incl, VP-2122incl, VP-2122, VP-2064,
 VP-2064incl, VP-3504, VP-3154, VP-3304,
 SX-2000SM, VX-2000, VX-3008F, VX-3004F,
 VX-3016F

Specifications

Frequency response	80 Hz - 20 kHz
Connection	Push wire connection (Bridging terminal - 2 branch type)
Sensitivity (1#V, 1#n) (combined)	94 dB (500 Hz - 5 kHz, pink noise)
Speaker component	12 cm cone-type
Rated input	6 W, 3 W
Tappings	6/3/1,5/0.8 W (100V) 3/1.5/0.8/0.4 W (70V)
Mounting hole	150,00 mm
Dimensions (W x H x D)	x 70
Dimensions (ø x D)	180 x 70 mm
Finish	Steel plate, paint, traffic white (RAL 9016 or equivalent)
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)



EN 54 certified speakers

PC-1860EN

Appearance