

Stylish design inspired by modern lighting fixtures Ideally suited for BGM & announcements 8 Ω and 25 V/70 V/100 V operation Input impedance is easily changed with a rotary switch on the top of the speaker With speaker cable, GRIPPLE® hanging wire & safety wire pre-attached, for faster, easier and more secure installation UL certified: UL Code: UL1480 UUMW, ULC-S541 Bass-reflex type



Order no: PE-604BU

Specifications

Frequency response	110 Hz - 20 kHz (-10 dB from sensitivity)
Sensitivity (1#V, 1#m) (combined)	90 dB (330 Hz – 3.3 kHz, pink noise)
Speaker component	12 cm cone-type + balanced-dome tweeter (coaxial)
Rated input	60 W
Tappings	100V line: 170 Ω (60W), 330 Ω (30W), 670 Ω (15W), 3.3k Ω (3W) 70V line: 83 Ω (60W), 170 Ω (30W), 330 Ω (15W), 670 Ω (7.5W), 3.3k Ω (1.5W) 25V line: 83 Ω (7.5W), 170 Ω (3.7W), 330 Ω (1.9W), 70 Ω (0.9W), 3.3k Ω (0.2W) Low impedance: 8 Ω
Rated impedance	100 V, 70 V, 8 Ω
Weight	2,9 kg
Certificates	UL, Ease
Dimensions (W x H x D)	x 275
Dimensions (ϕ x D)	186
Gross weight	4,46 kg
Finish	HIPS resin, black (RAL 9011 or equivalent)

Appearance

