

SR-S4LWP

LINE ARRAY SPEAKER

The SR-S4LWP is a weather-proof two-way line array speaker ideal for long distance sound transmission and configures a line array by arranging speaker elements vertically close to each other. It satisfies the water protection requirements set down in the IPX4 Standard. It can be converted into the bi-amplifier drive system by changing the internal connection. It can be used for high-impedance applications with the installation of the optional MT-S0601 Matching transformer.



Order no: SR-S4LWP

Specifications

Frequency response	70 Hz - 20 kHz
Connection	Direct cable withdrawal from internal speaker: ø8.6 mm, conductor cross section:1.25 mm ² , 4-core cable, 3 m
Sensitivity (1#V, 1#m) (combined)	94 dB
Speaker component	Low frequency: 10 cm cone-type × 8, High frequency: 2.5 cm balanced dome-type × 24
Directivity angle horizontal	90 °
Rated impedance	8 Ω
Crossover frequency	4 kHz
Power handling capacity	Continuous program: 600 W
Weight	16,0 kg
Certificates	IPX4, Ease
Dimensions (W x H x D)	160 x 895 x 255 mm
Dimensions (ø x D)	x 255 mm
Gross weight	18,9 kg
Finish	Plywood, urethane coating, off-white (RAL 9010 or equivalent)

SR-S4LWP

LINE ARRAY SPEAKER

Appearance

