

SR-S4S

LINE ARRAY SPEAKER

The SR-S4S is a two-way line array speaker ideal for short distance sound transmission and configures a line array by arranging speaker elements vertically close to each other. It can be converted into the bi-amplifier drive system by changing the internal connection. It can be used for high-impedance applications with the installation of the optional MT-S0601 Matching transformer.



Order no: SR-S4S

Specifications

Frequency response	70 Hz - 20 kHz
Connection	M5 screw terminal, distance between barriers: 12.2 mm and Neutrik NL4MP x 2 (usable cable connector: Neutrik NL4FC)
Sensitivity (1#V, 1#m) (combined)	93 dB
Speaker component	Low frequency: 10 cm cone-type x 8, High frequency: 2.5 cm balanced dome-type x 24
Directivity angle horizontal	90 °
Directivity angle vertical	10 °
Rated impedance	8 Ω
Crossover frequency	4 kHz
Power handling capacity	Continuous program: 600 W
Weight	16,0 kg
Certificates	Ease
Dimensions (W x H x D)	160 x 892 x 303 mm
Dimensions (ø x D)	x 303 mm
Gross weight	19,4 kg
Finish	MDF, paint, off-white (RAL 9010 or equivalent)

SR-S4S

LINE ARRAY SPEAKER

Appearance

