

One of the most difficult speaker requirements to satisfy is a cost-effective mid-size speaker system that offers high quality sound no matter what the application. TOA HS-Series speakers are equipped with narrow-directivity control (90° horizontal × 40° vertical). This useful feature allows tailoring the speaker's dispersion characteristics to better suit the acoustic environment in which it is installed. The versatile HS-Series is compatible for use with 100V/70V lines for distributed applications. The HS-Series speakers are exceptional in offering useful features at an attractive price.




Order no: HS-150W


## Specifications

Frequency response	70 Hz - 20 kHz
Connection	Neutrik NL4MP Speakon and M4 screw terminal, distance between barriers: 9 mm
Sensitivity (1#V, 1#m) (combined)	98 dB
Speaker component	38 cm cone-type, balanced dome-type x 6
Rated impedance	8 Ω
Power handling capacity	Continuous pink noise: 100 W Continuous program: 300 W
Dimensions (W x H x D)	451 x 560 x 400 mm
Dimensions (ø x D)	x 400 mm
Finish	Polypropylene resin, off-white (RAL 9010 or equivalent)
Operating temperature	-10 °C to +50 °C


Appearance




Front View



Side View



Rear View



Bottom View






Figure of the unit installed  
(scale: 1/15)



Wiring Diagram



ST-34B (option) mounting  
(scale: 1/20)

UNIT:mm SCALE:1/10