

DESCRIPTION

TOA Slim Array Speaker is a two way speaker which contain 32 speakers element, 8x 10cm woofer and 24x 2.5cm dome tweeter. Driver is installed vertically in order to create a linear sound source for indoor use, such as house of worship, lecture theater or multi purpose hall.

SPECIFICATIONS

Enclosure	Bass Reflex Type	
Max Input Power	Continuous	: 240 W
	Program	: 480 W
Rated Impedance	8 Ω	
Sensitivity	94 dB (1 W, 1 m)	
Frequency Response	95 - 20,000 Hz	
Crossover Frequency	2500 Hz	
Directivity	Horizontal : 100°, Vertical : 5°	
Speaker Component	Low Frequency	: 10 cm (4") Cone Type Woofer x8
	High Frequency	: 2.5 cm (1") Balanced Dome Tweeter x24
Input Connector	M4 Screw Terminal x 2	
Operating Temperature	-10° ~ +50° C	
Finish	Enclosure	: White Painted MDF Board
	Net Grille	: White Painted SPCC Punched Net
Dimensions	160 (W) X 950 (H) x 262 (D) mm	
Weight	17 kg	
Accessories	Mounting Bracket x 2	
Option	Flying Bracket	: SR-FB4
	Wall Tilt Bracket	: SR-TB4
	Extension Plate	: SR-EP4
	Wall Mounting Bracket	: SR-WB4
	Stand Adaptor	: SR-SA4
	Floor Stand	: SR-FS4
	Matching Transformer	: MT-S0601
	(for High Impedance)	

APPEARANCE

