

# VM-3240E

VM EXTENSION AMPLIFIER 240W



Order no: VM-3240E CE

## Specifications

|                        |  |
|------------------------|--|
| Power source           | 230 V AC, 50 / 60 Hz   |
| Rated output           | 240 W (total into 6 zones)   |
| Frequency response     | 50 Hz - 20 kHz (at 1/3 rated output)   |
| Distortion             | < 0.7 %  |
| Distortion             | < 0.7 %  |
| Power consumption      | 600 W (with rated output signal), 260 W (according to EN 60065)  |
| S/N ratio              | 85 dB (or more)  |
| Inputs                 | External amplifier Input: 100 V Line removable terminal block (14 pins)Local input -50 dBV (Mic) / -10 dBV (Line), 600 Ω / electronically balanced, removable terminal block (14 x 2 pins) |
| Outputs                | Speaker output 1 - 6: Total within rated output, removable terminal block (14 pins)Direct output from internal or external amplifier, removable terminal block (16 pins)                   |
| Control input          | Input 1 - 8: No-Voltage make contact input, open voltage: 24 V DC, short-circuit current: under 2 mA, removable terminal block (14 pins)   |
| Control output         | Output 1 - 8: Isolated open collector output, withstand voltage: 30 V DC, operating current: under 10 mA, removable terminal block (14 pins)   |
| Indicator              | Power; 5-segment bargraph level meter, selected zone, emergency zone active, communication fault, CPU fault  |
| Dimensions (W x H x D) | 482 x 132,6 x 407 mm   |
| Dimensions (ø x D)     | x 407 mm   |
| Finish                 | Aluminium, Steel plate, hairline, surface-treated, paint, black  |
| Operating humidity     | 5 to 95% RH (no condensation)  |
| Operating temperature  | -5°C to +45°C  |

# VM-3240E

VM EXTENSION AMPLIFIER 240W

## Appearance

